

# WASHDOWN HOSE ASSEMBLY

**HOT WATER HOSE FOR WASHDOWN STATIONS**



Cost effective, high quality washdown hose assemblies designed to complement the HCS and HCX Water Washdown Stations. Available in Black General Purpose or White Creamery versions.

## DESIGN FEATURES

- 4 ply textile reinforcement
- EPDM Tube
- White or black EPDM cover
- Brass and Zinc plated steel swivel fittings
- Strain relief coupling on station end.
- 300 PSIG max. operating pressure
- 200°F max. operating temperature
- 1/2" MNPT x 3/4" MNPT end connections
- Not for Steam Service



## DIMENSIONS & CAPACITIES

Type	I.D.	Nominal O.D.		Weight (per 100ft.)		Maximum Operating Pressure	Maximum Operating Temperature
		in.	mm.	Lb.	Kg.		
White Creamery	3/4"	1.25	31.8	48	22	300 PSIG/20.7 BAR	200° F/93.3°C
Black General Purpose	3/4"	1.156	29.4	37	17	300 PSIG/20.7 BAR	200° F/93.3°C

## ORDERING INFORMATION

Part Number	Description	Part Number	Description
940 - 000100 - 025	25 Ft. Black Hose Assembly	940 - 100100 - 025	25 Ft. White Creamery Hose Assembly
940 - 000100 - 050	50 Ft. Black Hose Assembly	940 - 100100 - 050	50 Ft. White Creamery Hose Assembly
940 - 000100 - 075	75 Ft. Black Hose Assembly	940 - 100100 - 075	75 Ft. White Creamery Hose Assembly



ThermOmegaTech®, Inc.  
353 Ivyland Road  
Warminster, PA 18974

1-877-379-8258  
www.ThermOmegaTech.com

WASHDOWNHOSE  
REV: 7/12/18

